

In the Claims

1-112. (Cancelled).

113. **(Currently Amended)** A communications device comprising:  
a subsystem, wherein  
the subsystem comprises a communications interface; and  
a logging module coupled to the subsystem, wherein  
the logging module is configured to periodically communicate information  
regarding a configuration of the subsystem, and  
the logging module is further configured to restrict a change to a  
configuration of the logging module by the subsystem.

114. **(Currently Amended)** The communications device of claim 113, wherein  
the logging module is further configured to restrict **[[a]] the** change to **[[a]] the**  
configuration of the logging module **[[by]] via** the communications interface.

115. **(Original)** The communications device of claim 113, wherein  
the logging module is configured to periodically communicate the information by virtue  
of being configured to automatically transmit a first copy of a configuration of the  
subsystem at a first time and a second copy of a configuration of the subsystem at  
a second time.

116. **(Original)** The communications device of claim 115, wherein  
the logging module is further configured to communicate the information to a security  
monitor coupled to the communications device.

117. **(Original)** The communications device of claim 116, wherein  
the security monitor is configured to detect a change in a configuration of the subsystem  
by a comparison of the first and the second copies.

118. (Original) The communications device of claim 117, wherein the security monitor is configured to set the communications device to an “untrustworthy” status in response to the change.
119. (Original) The communications device of claim 118, wherein the security monitor is configured to disconnect the communications device from the network in response to the communications device being set to the “untrustworthy” status.
120. (Original) The communications device of claim 117, wherein the logging module is further configured to restrict the subsystem from broadcasting using a logging module network address and a logging module communications protocol.
121. (Cancelled)
122. (Original) The communications device of claim 113, wherein the logging module is further configured to broadcast a data packet using a logging module network address and a logging module communications protocol.
123. (Original) The communications device of claim 122, wherein the logging module is further configured to communicate the information by broadcasting the data packet, wherein the data packet comprises at least a portion of the information.
124. (Original) The communications device of claim 123, wherein the logging module is configured to broadcast the information to a security monitor coupled to the subsystem via a network.

125. (Original) The communications device of claim 124, wherein the security monitor is configured to set the communications device to an “untrustworthy” status in response to the information indicating a change to the configuration of the subsystem.
126. (Original) The communications device of claim 125, wherein the security monitor is configured to disconnect the communications device from the network in response to the communications device being set to the “untrustworthy” status.
127. (Original) The communications device of claim 122, wherein the logging module is further configured to restrict the subsystem from broadcasting using the logging module network address and the logging module communications protocol.
128. (Original) The communications device of claim 127, wherein the logging module is further configured to broadcast using a logging module network address and a logging module communications protocol.
129. (Currently Amended) The communications device of claim 128, wherein the logging module is further configured to restrict **[[a]] the** change to **[[a]] the** configuration of the logging module **[[by]] via** the communications interface.
130. (Original) The communications device of claim 128, wherein the logging module is further configured to broadcast the information to a security monitor coupled to the communications interface via a network.
131. (Currently Amended) A method comprising:  
periodically communicating information regarding a configuration of a subsystem of a communications device, wherein  
the information is regarding an occurrence of a change in the configuration,  
and

**the subsystem comprises a communications interface.**

132. (Cancelled)

133. (Currently Amended) The method of claim ~~[[132]]~~ 131, further comprising:  
detecting the change.

134. (Cancelled)

135. (Currently Amended) The method of claim ~~[[134]]~~ 131, wherein the periodically communicating comprises:  
periodically broadcasting the information to a security monitoring process executing on a security monitor communicatively coupled to the communications interface.

136. (Original) The method of claim 135, further comprising:  
causing the security monitoring process to set the communications device to an “untrustworthy” status in response to the security monitoring process failing to receive the information within a time period.

137. (Original) The method of claim 136, further comprising:  
disconnecting the communications device from the network in response to the security monitoring process setting the communications device to the “untrustworthy” status.

138. (Original) The method of claim 131, further comprising:  
determining the configuration.

139. (Cancelled)

140. (Original) The method of claim 138, wherein  
the information comprises a change in the configuration.

141. (Original) The method of claim 138, further comprising:  
executing a logging process in a logging module of the communications device, wherein  
the logging process performs the periodically communicating information.
142. (Original) The method of claim 141, further comprising:  
detecting a change in the configuration, wherein the logging process performs the  
detecting.
143. (Cancelled)
144. (Currently Amended) The method of claim ~~[[143]]~~ 141, wherein the  
periodically communicating comprises:  
periodically broadcasting the information using the communications interface.
145. (Original) The method of claim 144, wherein the periodically broadcasting is  
performed using:  
a logging module network address, and  
a logging module communications protocol.
146. (Original) The method of claim 144, wherein the periodically broadcasting  
comprises:  
periodically broadcasting the information to a security monitoring process executing on a  
security monitor coupled to the communications interface via a network.
147. (Original) The method of claim 146, further comprising:  
setting the communications device to an “untrustworthy” status in response to receiving  
the information, wherein the setting is performed by the security monitoring  
process.
148. (Original) The method of claim 147, further comprising:  
disconnecting the communications device from the network in response to the setting the  
communications device to the “untrustworthy” status.

149. (Currently Amended) The method of claim ~~[[143]]~~ 141, further comprising:  
executing a communications process in the communications interface according to a configuration of the communications interface.

150. (Original) The method of claim 149, further comprising:  
restricting a change to the configuration of the logging module by the communications process.

151. (Original) The method of claim 150, wherein the executing the logging process further comprises:  
periodically broadcasting via the communications interface using a logging module network address and a logging module communications protocol.

152. (Original) The method of claim 151, wherein the executing the logging process further comprises:  
restricting the communications process such that the communications process cannot broadcast using the logging module network address and the logging module communications protocol.

153. (Original) The method of claim 138, wherein the periodically communicating comprises:  
periodically broadcasting the information using the subsystem.

154. (Original) The method of claim 153, wherein the periodically broadcasting is performed using:  
a logging module network address, and  
a logging module communications protocol.

155. (Original) The method of claim 154, wherein the periodically broadcasting comprises:

periodically broadcasting the information to a security monitoring process executing on a security monitor coupled to the communications device via a network.

156. (Original) The method of claim 155, further comprising:  
setting the communications device to an “untrustworthy” status in response to receiving the information, wherein the setting is performed by the security monitoring process.

157. (Original) The method of claim 156, further comprising:  
disconnecting the communications device from the network in response to the setting the communications device to the “untrustworthy” status.

158. (Currently Amended) A communications device comprising:  
**a logging module;**  
**a communications interface;**  
a subsystem, **wherein**  
**the subsystem and the logging module are coupled to one another, and**  
**the subsystem comprises the communications interface; [[and]]**  
means for periodically communicating information regarding a configuration of the subsystem, wherein  
the means for periodically communicating information is coupled to the subsystem;  
**means for determining the configuration; and**  
**means for executing a logging process in the logging module, wherein**  
**the logging process causes the periodically communicating information.**

159. (Cancelled)

160. (Currently Amended) The communications device of claim ~~[[159]]~~ 158, wherein the means for periodically communicating comprises:

means for periodically broadcasting the information to a security monitoring process  
executing on a security monitor communicatively coupled to the communications  
interface.

161. (Original) The communications device of claim 160, further comprising:  
means for causing the security monitoring process to set the communications device to an  
“untrustworthy” status in response to the security monitoring process failing to  
receive the information within a time period.

162. (Original) The communications device of claim 161, further comprising:  
means for disconnecting the communications device from the network in response to the  
security monitoring process setting the communications device to the  
“untrustworthy” status.

163. (Cancelled)

164. (Currently Amended) The communications device of claim ~~[[163]]~~ 158, wherein the means for periodically communicating comprises:  
means for periodically broadcasting the information using the communications interface.

165. (Original) The communications device of claim 164, wherein the means for  
periodically broadcasting comprises:  
means for periodically broadcasting the information to a security monitoring process  
executing on a security monitor coupled to the communications interface via a  
network.



166. (Original) The communications device of claim 165, further comprising:  
means for setting the communications device to an “untrustworthy” status in response to  
receiving the information, wherein the setting is performed by the security  
monitoring process.

167. (Original) The communications device of claim 166, further comprising:  
means for disconnecting the communications device from the network in response to the  
setting the communications device to the “untrustworthy” status.

168. (Original) The communications device of claim 166, further comprising:  
means for executing a communications process in the communications interface  
according to a configuration of the communications interface.

169. (Original) The apparatus of claim 168, further comprising:  
means for restricting a change to the configuration of the logging module by the  
communications process.

170. (Currently Amended) The ~~communications device~~ apparatus of claim  
169, wherein the means for executing the logging process further comprises:  
means for periodically broadcasting via the communications interface using a logging  
module network address and a logging module communications protocol.

171. (Currently Amended) The ~~communications device~~ apparatus of claim  
170, wherein the means for executing the logging process further comprises:  
means for restricting the communications process such that the communications process  
cannot broadcast using the logging module network address and the logging  
module communications protocol.

172. (Currently Amended) A computer program product comprising:  
a first set of instructions, executable on a computer system, configured to periodically  
communicate information regarding a configuration of a subsystem of a  
communications device;

**a second set of instructions, executable on said computer system, configured to determine the configuration;**

**a third set of instructions, executable on said computer system, configured to execute a logging process in a logging module of the communications device, wherein the logging process comprises the second set of instructions, and the subsystem comprises a communications interface; and**

computer readable **storage** media, wherein said computer program product is encoded in said computer readable **storage** media.

173. (Cancelled)

174. (Currently Amended) The computer program product of claim [[173]] **172**, wherein said first set of instructions comprises:

a first subset of instructions, executable on said computer system, configured to periodically broadcast the information to a security monitoring process executing on a security monitor communicatively coupled to the communications interface.

175. (Currently Amended) The computer program product of claim 174, further comprising:

a ~~second~~ **fourth** set of instructions, executable on said computer system, configured to cause the security monitoring process to set the communications device to an “untrustworthy” status in response to the security monitoring process failing to receive the information within a time period.

176. (Currently Amended) The computer program product of claim 175, further comprising:

a ~~third~~ **fifth** set of instructions, executable on said computer system, configured to disconnect the communications device from the network in response to the security monitoring process setting the communications device to the “untrustworthy” status.

177. (Cancelled)

178. (Currently Amended) The computer program product of claim ~~[[177]]~~ 172, wherein said first set of instructions comprises:

a first subset of instructions, executable on said computer system, configured to periodically broadcast the information using the communications interface.

179. (Original) The computer program product of claim 178, wherein said first subset of instructions comprises:

a first sub-subset of instructions, executable on said computer system, configured to periodically broadcast the information to a security monitoring process executing on a security monitor coupled to the communications interface via a network.

180. (Original) The computer program product of claim 179, further comprising: a fourth set of instructions, executable on said computer system, configured to set the communications device to an “untrustworthy” status in response to receiving the information, wherein the setting is performed by the security monitoring process.

181. (Currently Amended) The computer program product of claim 180, further comprising:

a ~~fourth~~ fifth set of instructions, executable on said computer system, configured to disconnect the communications device from the network in response to the setting the communications device to the “untrustworthy” status.

182. (Currently Amended) The computer program product of claim ~~[[177]]~~ 172, further comprising:

a fourth set of instructions, executable on said computer system, configured to execute a communications process in the communications interface according to a configuration of the communications interface.

183. (Original) The computer program product of claim 182, further comprising:  
a fifth set of instructions, executable on said computer system, configured to restrict a  
change to the configuration of the logging module by the communications  
process.

184. (Original) The computer program product of claim 183, wherein said third set  
of instructions comprises:

a first subset of instructions, executable on said computer system, configured to  
periodically broadcast via the communications interface using a logging module  
network address and a logging module communications protocol.

185. (Original) The computer program product of claim 184, wherein said third set  
of instructions further comprises:

a second subset of instructions, executable on said computer system, configured to  
restrict the communications process such that the communications process cannot  
broadcast using the logging module network address and the logging module  
communications protocol.